

PRODUCT SPECIFICATIONS

Detail Photos

(on right from top to bottom)

Pre-assembled Az/EI Mount
(73-76 mm)

Fine-elevation adjustment
with stamped degree scale

Ku feed assembly with LNB
cover



1.0 m Receive-Only Antenna System

TYPE 100

The reflector is thermoset-molded for strength and surface accuracy.

The Skyware Global 1.0 m Type 100 Offset Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain its critical parabolic shape.

The Az/EI mount is constructed from heavy-gauge steel to provide a rigid support to the reflector. The Az/EI mount secures the antenna to either a 60 mm (2.38") or 73-76 mm (2.88"-3.00") O.D. mast and prevents slippage in high winds.

A specially formulated powder paint process offers excellent protection from weather-related corrosion.

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- One-piece thermoset-molded offset reflector.
- Single bolt fine elevation adjustment.
- Galvanized 19 mm (.75") O.D. feed support legs.
- Factory pre-assembled Az/EI mount.
- Plated hardware for maximum corrosion resistance.
- Available with a wide variety of Ku-band feeds.



Satcom solutions for the long haul

REV 03/15-02
Page 1 of 2

•PRODUCT SPECIFICATIONS

RF Performance

Effective Aperture 1.0m (40in)
 Operating Frequency 10.95 - 12.75 GHz
 Polarization..... Linear, Orthogonal
 Gain @40.5 dBi
 3 dB Beamwidth1.95°
 Antenna Noise Temperature
 30° EL..... 25°K
 VSWR* 1.3:1
 Cross-Polarization Discrimination (Linear).....
 30 dB on Axis
 Feed Interface WR75 Flat Flange

(All specifications typical)

*Function of feed specifications

1.0m Receive Only Antenna System

Mechanical Performance

Reflector Material.....Glass Fiber Reinforced Polyester
 Antenna Optics One-Piece Offset Feed Prime Focus
 Mount Type Elevation over Azimuth
 Elevation Adjustment Range10° - 70° Continuous
 Fine Adjustment (60mm)
10° - 90° Continuous
 Fine Adjustment (73mm)
 Azimuth Adjustment Range360° Continuous,
 Mast Pipe Interface......60mm (2.38 in)
 73-76(2.88 in - 3.00 in) Diameter

Environmental Performance

Wind Loading

Operational..... 50 mph (80 km/h)
 Survival 125 mph (200 km/h)
 Temperature -50°C to +80°C
 Humidity.....0 to 100% (Condensing)
 Atmosphere..... Standard Hardware 500 Hrs SST
 Requirements (ASTM B-117)
 Solar Radiation360 BTU/h/ ft²
 Shock and Vibration..... As Encountered during
 Shipping and handling



REV 03/15-02
Page 2 of 2